



Affordable Wide Belt Sander , MS13RR Big Belt Sander Machine Manufacturer

Our Product Introduction

for more products please visit us on skdmachinery.com

Basic Information

- Place of Origin: China
- Brand Name: SKD
- Model Number: MS13RR
- Minimum Order Quantity: 1 set
- Price: USD10000-350000
- Packaging Details: Shrink Wrapped or Woodcase
- Delivery Time: 20-60 days
- Payment Terms: TT
- Supply Ability: 70-100set per year



Product Specification

- Name: Big Belt Sander Machine
- Type: Sanding
- Model: MS13RR
- Function: Deburring, Grinding, Slag Removal, Finishing
- Max Working Width: 1350mm
- Power: 380v 50Hz Or Customized
- Highlight: **Affordable Wide Belt Sander Machine, Big Belt Sander Machine Manufacturer, MS13RR Big Belt Sander Machine**



More Images



Product Description

Metal Wide Belt Sander

General Description

This is a metalworking wide belt sander for deburring, sanding, polishing, finishing, slag removal and texturing. With 2 powerful sanding drums and vacuum sucking work-table, the metal wide belt sander can process wide metal sheets, plates, middle and small size metal work-piece in an effective way for deburring, grinding and finishing. With a quick change of the abrasive belt, this metal wide belt sander can do slag removal and oxide removal of the metal parts done by plasma cut or flame cut.

The wide belt sander typically incorporates adjustable settings for controlling the speed of the conveyor belt, the pressure applied to the workpiece, and the type of abrasive used. This allows operators to achieve the desired level of surface finish and remove material to precise specifications. Some advanced models may also include additional features such as automated feeding systems, digital controls, and multiple sanding heads for increased versatility and productivity.

SPECIFICATIONS

Abrasive Belt Size 2500x1380mm
Motor : 22kw +22kw with frequency control
Table Lifting Motor: 1.5kw
Number of Heads :2
Sanding Drum Diameter: 240mm
Work piece fix :Vacuum
Vacuum Area:1250×200mm
Speed setting of sanding drum: Frequency converter control
Sanding Drum RPM: 1720
Power supply: 380v 50Hz or on request
Dust port size: drum 150mm x 6, space 100mm x 4
Automatic Thickness Control: Yes (Thickness or)
Foot Print: 51-1/2" x 19"
Sanding Belt Oscillation: Yes
Sanding Belt Motor Break: Yes
Conveyor Opening 0-80mm
Floor to Table Height 900-990mm
Conveyor Drive Motor 5.5kw
Feed Speed 5-25 meter per minute variable
Dimension 2200x2500x2300mm WxDxH
Weight 3.9 ton
Work piece Max Width 1350mm
Work piece Max Thickness 60mm
Work piece Min. Length 100mm



SHOT ON MI 10 5G





SKD Machinery(Qingdao)Co. Ltd.



+86 186 5321 8199



skdmachinery@126.com



skdmachinery.com

Workshop C-16 No.1 Zhenping Road,Sifang,Qingdao