

China SKD

20-60 days

70-100set per year

ΤT

Customized Metal Wide Belt Sander 380V 50HZ For Slag Removal / Texturing

Basic Information

- Place of Origin:
- Brand Name:
- Model Number: MS13RRMinimum Order Quantity: 1 set
- Price: USD10000-350000
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Name:
- Contact Drum:
- Feature:
- Control Panel:
- Power:
- Number Of Heads:
- Highlight:

Metal Wide B	elt Sander
--------------	------------

Shrink Wrapped or Woodcase

High Quality

- Robust Welded Frame
- Control Panel With Motor Load Meter, digital Readout
- 380V 50HZ Or Customized
- 2
 - Customized Metal Wide Belt Sander, Metal Wide Belt Sander 380V, Metal Slag Removal Machine 50HZ



Metal Wide Belt Sander

General Description

This is a metalworking wide belt sander for deburring, sanding,polishing, finishing, slag removal and texturing. With 2 powerful sanding drums and vacuum sucking work-table, the metal wide belt sander can process wide metal sheets, plates,middle and small size metal work-piece in an effective way for deburring, grinding and finishing. With a quick change of the abrasive belt, this metal wide belt sander can do slag removal and oxide removal of the metal parts done by plasma cut or flame cut.

The metal wide belt sander is designed for one wide part or multi smaller parts processed in a production line or in an independent way. Vacuum sucking work-table can fix minimum 100mm smaller parts on the conveyor belt to insure a good deburring or finishing. Either high productivity in a flow line or reliable effects for smaller parts, this metal wide belt sander will not let you down, but saving labor and time.

FEATURES

1350mm max working width Digital thickness readout for conveyor height Control panel with motor load meter,digital readout Electronic abrasive belt tracking Pneumatic abrasive tensioning SPECIFICATIONS

Abrasive Belt Size 2500x1380mm Motor : 22kw +22kwwith frequency control Table Lifting Motor: 1.5kw Number of Heads : 2 Sanding Drum Diameter: 240mm Work piece fix : Vacuum Vacuum Area:1250×200mm Speed setting of sanding drum: Frequency converter control Sanding Drum RPM: 1720 Power supply: 380v 50Hz or on request Dust port size: drum 150mm x 6, space 100mm x 4 Automatic Thickness Control: Yes (Thickness or) Foot Print: 51-1/2" x 19" Sanding Belt Oscillation: Yes Sanding Belt Motor Break: Yes Conveyor Opening 0-80mm Floor to Table Height 900-990mm Conveyor Drive Motor 5.5kw





Workshop C-16 No.1 Zhenping Road, Sifang, Qingdao