



Durable 24 Inch Wide Belt Sander Machine Small Footprint 1000 Series

Our Product Introduction

for more products please visit us on skdmachinery.com

Basic Information

- Place of Origin: China
- Brand Name: SKD
- Model Number: 1000-series
- Minimum Order Quantity: 1 set
- Price: USD10000-350000
- Packaging Details: Shrink Wrapped or Woodcase
- Delivery Time: 20-60 days
- Payment Terms: TT
- Supply Ability: 70-100set per year



Product Specification

- Name: 24 Inch Wide Belt Sander Machine
- Belt Width: 13 Inch To 43 Inch
- Motor Size: 5 HP To 30 HP
- Number Of Heads: 1 To 3
- Types Of Heads: Drum, Scotch-Brite, Brush And Disc
- Drum Size: 100 Mm To 200 Mm
- Highlight: **Durable Wide Belt Sander Machine,
24 Inch Wide Belt Sander Machine,
24 Inch Wide Belt Sander Small Footprint**



Product Description

Wide Belt Grinder

The 1000-series of machines are built in a heavy duty construction with a smaller footprint designed to accommodate a job shop with various applications such as deburring, dross removal, calibrating/dimensioning, edge radiusing or finishing. This series of machine can be built in both top and bottom configurations.

1000 series machines are suitable for a wide range of applications, including but not limited to the following:

Metal Processing: These machines can be used in the metal processing industry for processes such as deburring, corner trimming, dimensional alignment, surface polishing, etc. They can handle various metal materials such as steel, aluminum, copper, etc.

Manufacturing: 1000 series machines are widely used in manufacturing processes such as welding slag removal, oxide layer removal, smoothing/calibrating dimensions, corner rounding or surface finishing, etc. They can be used in various manufacturing fields such as automobile manufacturing, aerospace, electronic equipment, etc.

MACHINE FEATURES

1. Machines built in widths from 13" to 43" and multiple head frames
2. Dual infeed and outfeed pinch rolls to ensure parts feed through machine properly
3. One- to three-head configurations with drum, brush, disc or combination drum/brush/disc heads
4. Individual cam adjustment down to .001" per head for accurate finishing
5. Air-loaded cylinder for automated belt tensioning
6. Automatic abrasive belt tracking to ensure proper belt alignment during operation



SKD Machinery(Qingdao)Co. Ltd.



+86 186 5321 8199



skdmachinery@126.com



skdmachinery.com

Workshop C-16 No.1 Zhenping Road,Sifang,Qingdao