



Versatile Deburring Oxide Removal Machine For Edge Rounding / Orbital Finishing In One Pass

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: SKD
- Minimum Order Quantity: 1 set
- Price: USD10000-350000
- Packaging Details: Shrink Wrapped or Woodcase
- Delivery Time: 20-60 days
- Payment Terms: TT
- Supply Ability: 70-100set per year



Product Specification

- Name: Deburring Oxide Removal Machine
- Origin: China
- Working Widths: 1000mm, 1500mm And 2000mm
- Material Thickness: 0,3mm – 70mm (100mm)
- Machine: Versatile
- Feature: Deburring
- Highlight: **Deburring Oxide Removal Machine,
Versatile Oxide Removal Machine**

for more products please visit us on skdmachinery.com

Product Description

Metal Deburring Machine

General

To properly clean your belt disc edger and ensure its optimal operation and longevity, follow these guidelines:

Turn off the machine: Before starting the cleaning process, ensure that the disc edger is turned off and disconnected from the power source for safety.

Remove residue: Use a brush or air pressure device to gently remove any large particles of residue, such as metal shavings or dust, from the machine's surfaces and individual components. If necessary, utilize a vacuum cleaner or air pressure device to collect loose residue.

Cleaning fluid: Select a suitable cleaning fluid based on the material being processed, such as deionized water, detergent, or a specialized metal cleaner. Refer to the manufacturer's recommendations and instructions for the correct detergent and concentration to use.

Avoid damage: Take care to prevent cleaning fluid or water from directly entering the machine's interior or coming into contact with electrical components. Instead, dampen a cloth or use a sprayer to apply the cleaning liquid onto the cloth, and gently wipe the surfaces and parts of the machine.

Drying and lubrication: After cleaning, thoroughly dry the machine's surfaces and components using a clean cloth or paper towel. For parts that require lubrication, apply an appropriate lubricant as recommended by the manufacturer.

Safety guards and safety devices: Clean and inspect the machine's safety guards and safety devices to ensure they are free from dirt, damage, and properly installed.

SPECIFICATIONS

Two large discs both at infeed side and outfeed side
Large oscillation stroke over full width of the feed belt
For deburring and edge rounding 3D punched parts
For edge rounding and orbital finishing in one pass
Working widths: 1000mm, 1500mm and 2000mm
Smallest part size: 20mm x 20mm
Material thickness: 0,3mm – 70mm (100mm)



SKD Machinery(Qingdao)Co. Ltd.



+86 186 5321 8199



skdmachinery@126.com



skdmachinery.com

Workshop C-16 No.1 Zhenping Road,Sifang,Qingdao