

Surface Deburring Machine Manufacturers , Versatile Wide Belt Deburring Machine

Basic Information

Place of Origin: ChinaBrand Name: SKDMinimum Order Quantity: 1 set

• Price: USD10000-350000

Packaging Details: Shrink Wrapped or Woodcase

• Delivery Time: 20-60 days

Payment Terms: TT

• Supply Ability: 70-100set per year



Product Specification

Name: Surface Deburring Machine
Working Widths: 1000mm, 1500mm And 2000mm
Material Thickness: 0,3mm - 70mm (100mm)

Machine: VersatileFeature: DeburringOrign: China

• Highlight: Surface Deburring Machine Manufacturers,

Wide Belt Surface Deburring Machine, Versatile Wide Belt Deburring Machine

Product Description

Metal Deburring Machine

General

To clean your belt disc edger and maintain its optimal performance, follow these steps:

Turn off the machine: Prior to cleaning, make sure the disc edger is powered off and disconnected from the power source for safety.

Remove residue: Use a brush or air pressure device to gently remove any large particles of residue, such as dust or metal shavings, from the machine's surfaces and individual components. If needed, employ a vacuum cleaner or air pressure device to collect loose residue.

Cleaning solution: Choose an appropriate cleaning fluid based on the material being processed. This may include deionized water, detergent, or a specialized metal cleaner. Refer to the manufacturer's recommendations and instructions for the correct detergent and concentration.

Prevent damage: Avoid direct contact of cleaning fluid or water with the machine's interior or electrical components. Instead, dampen a cloth or use a sprayer to apply the cleaning solution onto the cloth, and gently wipe the machine's surfaces and parts.

Drying and lubrication: After cleaning, thoroughly dry the surfaces and components using a clean cloth or paper towel. Apply a suitable lubricant to parts that require lubrication, following the manufacturer's recommendations.

Safety guards and devices: Clean and inspect the machine's safety guards and devices to ensure they are free from dirt, damage, and properly installed.

By following these guidelines, you can effectively clean your belt disc edger and maintain its performance and longevity.

SPECIFICATIONS

Two large discs both at infeed side and outfeed side Large oscillation stroke over full width of the feed belt For deburring and edge rounding 3D punched parts Working widths: 1000mm, 1500mm and 2000mm

Smallest part size: 20mm x 20mm

Material thickness: 0,3mm - 70mm (100mm)



SKD Machinery(Qingdao)Co. Ltd.



+86 186 5321 8199



skdmachinery@126.com



skdmachinery.com

Workshop C-16 No.1 Zhenping Road, Sifang, Qingdao