



Industrial Tool Wide Band Sander Customized For Deburring / Grinding

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: SKD
- Model Number: MS13RR
- Minimum Order Quantity: 1 set
- Price: USD10000-350000
- Packaging Details: Shrink Wrapped or Woodcase
- Delivery Time: 20-60 days
- Payment Terms: TT
- Supply Ability: 70-100set per year



Product Specification

- Name: Wide Band Sander
- Function: Deburring, Grinding, Slag Removal, Finishing
- Contact Drum: High Quality
- Work Piece Max Thickness: 60mm
- Table Lifting Motor: 1.5kw
- Number Of Heads: 2
- Highlight: **Industrial Tool Wide Band Sander,
Wide Band Sander Customized,
Industrial Wide Band Sander**



for more products please visit us on skdmachinery.com

Product Description

Metal Wide Belt Sander

General Description

A metal wideband sander, also known as a wideband sander or simply a wideband sander, is a powerful industrial tool used for sanding, polishing and finishing large metal surfaces. It consists of a horizontal conveyor belt, usually several inches wide, driven by electric rollers. The conveyor belt is coated with an abrasive material such as sandpaper or abrasive belts, allowing it to remove material from metal surfaces.

Metal wideband sanders are widely used in multiple industries including metal processing, automotive, aerospace, and manufacturing. They are designed to handle heavy-duty applications, capable of removing large amounts of material quickly and efficiently. These machines are typically used for tasks such as deburring, grinding welds, smoothing surfaces, and preparing metals for painting or coating.

Belt sanders typically have adjustable settings that control the speed of the belt, the pressure applied to the workpiece, and the type of abrasive used. This enables operators to achieve the desired surface finish and remove material to precise specifications. Some advanced models may also include additional features such as automatic feeding systems, digital controls, and multiple sanding heads to increase the machine's versatility and productivity.

SPECIFICATIONS

Power supply: 380v 50Hz or on request
Dust port size: drum 150mm x 6, space 100mm x 4
Automatic Thickness Control: Yes (Thickness or)
Foot Print: 51-1/2" x 19"
Sanding Belt Oscillation: Yes
Sanding Belt Motor Break: Yes
Conveyor Opening 0-80mm
Floor to Table Height 900-990mm
Conveyor Drive Motor 5.5kw
Feed Speed 5-25 meter per minute variable
Dimension 2200x2500x2300mm WxDxH
Weight 3.9 ton
Work piece Max Width 1350mm
Work piece Max Thickness 60mm
Work piece Min. Length 100mm



SHOT ON MI 10 5G



SKD Machinery(Qingdao)Co. Ltd.



+86 186 5321 8199



skdmachinery@126.com



skdmachinery.com

Workshop C-16 No.1 Zhenping Road,Sifang,Qingdao