



## Versatility Metal Wide Belt Sander Double Head For Deburring / Grinding / Finishing

Our Product Introduction

for more products please visit us on [skdmachinery.com](http://skdmachinery.com)

### Basic Information

- Place of Origin: China
- Brand Name: SKD
- Model Number: MS13RR
- Minimum Order Quantity: 1 set
- Price: USD10000-350000
- Packaging Details: Shrink Wrapped or Woodcase
- Delivery Time: 20-60 days
- Payment Terms: TT
- Supply Ability: 70-100set per year




### Product Specification

- Name: Metal Wide Belt Sander
- Type: Sanding
- Model: MS13RR
- Function: Deburring, Grinding, Slag Removal, Finishing
- Max Working Width: 1350mm
- Power: 380v 50Hz Or Customized
- Highlight: **Versatility Metal Wide Belt Sander, Metal Wide Belt Sander Double Head, Double Head Wide Belt Sander For Metal Finishing**



### More Images



## Product Description

### Metal Wide Belt Sander

#### General Description

This is a metalworking wideband sander for deburring, sanding, polishing, finishing, slag removal and texturing. Equipped with two powerful sanding drums and a vacuum suction table, it can efficiently handle wide metal sheets, metal plates, small and medium-sized metal workpieces for deburring, grinding and finishing. With quick belt changes, this metal wide belt sander removes slag and oxides from metal parts created by plasma or flame cutting.

Belt sanders typically have adjustable settings that control the speed of the belt, the pressure applied to the workpiece, and the type of abrasive used. This enables operators to achieve the desired surface finish and remove material to precise specifications. Some advanced models may also include additional features such as automatic feeding systems, digital controls, and multiple sanding heads to increase the machine's versatility and productivity.

#### SPECIFICATIONS

Abrasive Belt Size 2500x1380mm  
Motor : 22kw +22kwwith frequency control  
Table Lifting Motor: 1.5kw  
Number of Heads :2  
Sanding Drum Diameter: 240mm  
Work piece fix :Vacuum  
Vacuum Area:1250×200mm  
Speed setting of sanding drum: Frequency converter control  
Sanding Drum RPM: 1720  
Power supply: 380v 50Hz or on request  
Dust port size: drum 150mm x 6, space 100mm x 4  
Floor to Table Height 900-990mm  
Conveyor Drive Motor 5.5kw  
Feed Speed 5-25 meter per minute variable  
Dimension 2200x2500x2300mm WxDxH  
Weight 3.9 ton  
Work piece Max Width 1350mm  
Work piece Max Thickness 60mm  
Work piece Min. Length 100mm







**SKD Machinery(Qingdao)Co. Ltd.**



+86 186 5321 8199



skdmachinery@126.com



skdmachinery.com

Workshop C-16 No.1 Zhenping Road,Sifang,Qingdao